ADINSTRUMENTS

MLT5733 pH Electrode – Tuff Tip™

Transducer Series

The MLT5733 Tuff Tip™ pH Electrode is a combination electrode for measuring a wide pH range (0 to 13) at temperatures between –5 and 100°C. The electrode is constructed with the novel Magna-Flow™ reference junction and features a rugged pH bulb which is protected by its unique Tuff Tip™ shape. The large annular ceramic Magna-Flow™ reference junction and cross linked polymer gel are resistant to fouling, even in dirty samples. The durability of the electrode makes it ideal for student use. Suitable for use with the FE165 pH Amp or the ML303 pH Pod.

Caution

Read "Statement of Intended Use" on our website or in "Getting Started with PowerLab" before use.

Ordering Information:

MLT5733 pH Electrode-Tuff Tip™ For Student Use

For use with:
FE165 pH Amp
ML303 pH Pod

WARRANTY: ADInstruments PowerLab data acquisition units (Product Number Prefix: PL), Front-end Signal Conditioners (Product Number Prefix: FE) are warranted against defects in materials and workmanship for a period of 5 years from the date of purchase. Other PowerLab data acquisition units and ADInstruments manufactured Front-end and Pod Signal Conditioners, and Instruments are warranted of a period of 3 years from the date of purchase. Third party products are covered by the manufacturer's warranty. Warranties are void if the product has been damaged due to negligence. Consumables and electrodes are not covered by a warranty. All questions regarding service and warranty should be directed to your nearest ADInstruments representative.